

PRODUCT SPECIFICATIONS

ATTENUATOR 50W

MODEL JRT-ATxx-P-N050

Features:

- Excellent performance
- Wide frequency band
- Low VSWR
- Totally maintenance free



SPECIFICATIONS	
FREQUENCY RANGE	DC-3GHz
VSWR	<1.2:1
AVERAGE POWER	50W
PIM (IMD3)	<-120dBc @2x43dBm
IMPEDANCE	50 Ω
CONNECTOR	N-Male to N-Female
OPERATING TEMPERATURE	-30 to +65 $^{\circ}\text{C}$
DIMENSION	120mm x Φ 50mm
WEIGHT	0.285 Kg
FINISH	Black Plated

MODEL No.	ATTENUATION VALUE	ACCURACY
JRT-AT03-P-N050	3dB	$\pm 0.4\text{dB}$
JRT-AT06-P-N050	6dB	$\pm 0.4\text{dB}$
JRT-AT10-P-N050	10dB	$\pm 0.6\text{dB}$
JRT-AT15-P-N050	15dB	$\pm 0.6\text{dB}$
JRT-AT20-P-N050	20dB	$\pm 0.8\text{dB}$
JRT-AT30-P-N050	30dB	$\pm 0.8\text{dB}$
JRT-AT40-P-N050	40dB	$\pm 1.0\text{dB}$

PRODUCT DESIGN AND DIMENSIONS:

